

STAR PLUS

TUBULAR BATTERY E-RICKSHAW



Technical Specifications

Product Type (C20 rate - 27°C)	Dimensions (LWH) (mm) ± 5	Wet Weight (Kgs) ± 3%	Sp. Gr. – Full Charge - 27°C	Charging Amps	Free Replacement Warranty
12V 100 AH	410 X 174 X 247	28.00	1.265 ± 0.005	15A	06 Months
12V 120 AH	410 X 174 X 247	30.00	1.265 ± 0.005	16A	09 Months

Salient Features

- High Pressure Die Casted Tubular Spines
- Low Antimonial Selenium Alloy
- Best quality of Oxide formulation with additives
- Specially designed negative plates
- High Tensile, Acid Resistant Polyester Gauntlets
- High Porosity & Low Electrical Resistance Separators
- Corrosive Resistant Fasteners
- Superior Mileage Output, High number of Cycles, High Reliability & Guaranteed Service Life
- Low Self Discharge & Quick Recharge
- Factory filled and charged condition

Applications

Electric Rickshaw

AUTHORISED DEALER

- Plant and Office: Vill: Chakundi, Post: Dankuni Coal Complex (Township), Dist: Hooghly-712 310, West Bengal, India
- enquiry@starbattery.in
- 🌎 www.starbattery.in



