

STAR

TUBULAR BATTERY INVERTER / UPS



TECHNICAL SPECIFICATIONS

Product Type (C20 rate - 27°C)	Dimensions (LWH) (mm) ± 5	Wet Weight (Kgs) ± 3%	Sp. Gr. – Full Charge - 27°C	Charging Amps	Free Replacement Warranty
12V 150 AH TT	503 X 191 X 410	60.00	1.245 ± 0.005	12A	36 Months
12V 180 AH TT	503 X 191 X 410	63.00	1.245 ± 0.005	15A	36 Months
12V 220 AH TT	503 X 191 X 410	66.00	1.245 ± 0.005	18A	36 Months

Salient Features

- High Pressure Die Casted Tubular Spines
- Low Antimonial Selenium Alloy
- Best quality of Oxide formulation with additives
- Flat pasted negative plates
- High Tensile, Acid Resistant Polyester Gauntlets
- High Porosity & Low Electrical Resistance Separators
- Microporous Ceramic Vent Plugs with indicators
- Corrosive Resistant Fasteners
- Superior Performance, High Reliability & Guaranteed Service Life
- Suited for frequent and long power cuts
- Low Self Discharge & Quick Recharge
- Large electrolyte volume for minimum maintenance
- Factory filled and charged condition

Applications

- Domestic Inverter / UPS Systems
- EPABX Systems
- Alarm Systems
- Emergency Lighting

AUTHORISED DEALER

- Plant and Office: Vill: Chakundi, Post: Dankuni Coal Complex (Township), Dist: Hooghly-712 310, West Bengal, India
- enquiry@starbattery.in
- n www.starbattery.in

AN ISO 9001 & 14001 COMPANY

