

HIGH BACKUP
LONG LIFE | LOW MAINTENANCE

**STAR
PLUS**

**TUBULAR
BATTERY
SOLAR**



TECHNICAL SPECIFICATIONS

Product Type (C10 rate - 27°C)	Dimensions (L W H) (mm) ± 5	Wet Weight (Kgs) ± 3%	Sp. Gr. – Full Charge - 27°C	Charging Amps	Free Replacement Warranty
12V 20 AH	260 X 170 X 230	13.50	1.245 ± 0.005	2A	24 Months
12V 40 AH	410 X 174 X 247	23.20	1.245 ± 0.005	4A	36 Months
12V 60 AH	506 X 219 X 291	45.00	1.245 ± 0.005	6A	36 Months
12V 80 AH	506 X 219 X 291	49.00	1.245 ± 0.005	8A	36 Months
12V 100 AH	506 X 219 X 291	50.00	1.245 ± 0.005	10A	36 Months

2V Cells ranging from 200 Ah to 3000 Ah (upto 360V) also available for Off Grid Solar Power Plant applications. Kindly contact us for details.

Salient Features

- High Pressure Die Casted Tubular Spines
- Low Antimonial Selenium Alloy
- Best quality of Oxide formulation with additives
- Flat pasted negative plates
- High Tensile, Acid Resistant Polyester Gauntlets
- High Porosity & Low Electrical Resistance Separators
- Microporous Ceramic Vent Plugs
- Corrosive Resistant Fasteners
- Superior Performance, High Reliability & Guaranteed Service Life
- Available in 12V & 2V Series
- Suited for Deep Cycling duty & Partial State of Charge
- Factory filled and charged condition
- Conforms to latest BIS specifications

Applications

- Solar Home & Street Lighting System
- Solar Hybrid Inverter System
- Roof Top Solar Power Generation Plant
- Solar Fencing System
- Off – Grid Solar Power Plant
- Traffic / Railway Signaling System

AUTHORISED DEALER

📍 Plant and Office : Vill : Chakundi, Post :Dankuni Coal Complex (Township), Dist : Hooghly-712 310, West Bengal, India

✉ enquiry@starbattery.in

🌐 www.starbattery.in

AN ISO 9001 & 14001 COMPANY

